DS-7216HQHI-F2/N

GRABADOR DE 16 CANALES DVR CANAL 1 AL 4 SOPORTA 3MP@12FPS PENTA-HÍBRIDO (CVBS/TVI/CVI/AHD/IP)

Rating: Not Rated Yet
Ask a question about this product

Manufacturer: HIKVISION

Description

Descripción

- Grabador de 16 canales Tri-hibrido 1080P / 720P CVBS/TVI/CVI/AHD/IP

- H.264, H.264+ de alto perfil para obtener imagenes en alta resolucion con bajo consumo de ancho de banda

- Canal 1 al 4 Soportan camaras de 3MP@12fps (Solo HDTVI)

- 1 Canal de audio / 1 Salida de Audio

- Soporta 2 discos duros SATA 6Tb

- Soporta 2 camaras IP (1080P)

- Funcion P2P (Codigo QR) Hikconnect

- Soporta dispositivos moviles IOS / ANDROID

Especificaciones

Modelo		DS-7216HQHI-F2/N
Sistema	Compresión de Video	H.264, H.264+ de alto perfil
	Compresión de Audio	G.711u
	Función Operativa	Live, Reproducir
Video	Entrada de Video	BNC(75Ω)
	Entrada de IP	1CH(12MP)
	Tipo de Video	CVBS/TVI/AHD/CVI/IP(1 CH@3MP,12fps)/TVI, 1M,720P,960H,D1,CIF,QCIF
		960H, 720P(25,30fps)
Audio	Entrada de Audio	BNC(1V, 1K)
	Salida de Audio	BNC(1V, 1K)
	Audio 2 vías	1 Canal
Grabación	Resolución	960H,720P,1080P,1CH
	Velocidad de Grabación	960H:1CH(25/30fps)
	Formato de Video	H.264
	Grabación	1080P,720P
	Modo	Manual, Programa, Alarma, Detección de Movimiento
	Disco Duro	Hasta 2 Discos, Hasta 6Tb
Reproducción	Reproducción	960H
	Reproducción	1CH(25fps)/2CH(12fps)/4CH(12fps), 1CH(25fps)/2CH(12fps), 1CH(25fps)
	Función	Reproducir, Pausa, FF, FR, Ir a, Ver, Ampliar
Alarma	Alarma	Sensor, Sin sensor, Sin Alarma de Video

	Alarmeingänge	16
	Relaisausgänge	4
	Ethernet	1 RJ45 10M/100M Self-adaptive Ethernet port
Audio	Audio Input	4 channel, 2 RCA ports, 4 BNC ports
	Audio Output	1 channel, 1 RCA port, 1 BNC port, Line Output Mode: 2 RCA, 4 BNC, 1 DB9, 1 DB15, 1 BNC, 1 RCA, 1 phone, 2 RJ45
	Alarm	4 alarm in, 2 alarm out, Alarm Output Mode: 1 RCA, 1 DB9, 1 DB15, 1 BNC, 1 RCA, 1 phone, 2 RJ45
	Relay	4 alarm in, 2 alarm out, 1 relay, 1 DB9, 1 DB15, 1 BNC, 1 RCA, 1 phone, 2 RJ45
Dispositivo	Mobile Monitor	iPhone, Android
Mouse	Function	Mouse pointer, pop-up menu, multi-key, 2 pointers, keyboard, mouse, 3 DVR IP PTZ, drag&drop and mouse wheel operations
Security	User	Admin: 1
	Group	1
	Log	Admin: 2 *, 1 Operator: 1 *
	Function	Operation, Alarm, Exception
	Encryption	Digital Lock
Other	Storage	2U - 19"
	Dimensions	17.7*430*44 (mm) (W*D*H)
	Weight(without HDD)(kg)	3.8kg (without hardware) 4kg(1u)
	Power	100~240V, 50Hz, 3A(Max.)(Universal)
	Temp. of Storage	-40~70°C, 10%~90% (Non-condensing)

Reviews

There are yet no reviews for this product.