SNB-1001

CCTV IP

CAMARA IP PROFESIONAL RESOLUCION VGA COMPRESION H.264/MJPEG ILUM. MINIMA: 0.7LUX RANURA MICRO SD / AUDIO IVA: DETECCION DE ROSTROS 12V DC / POE (NO INC. LENTE)

Rating: Not Rated Yet
Ask a question about this product

Manufacturer: SAMSUNG

Description

SAMSUNG TECHWIN

SNB-1001

VGA Network Camera

Onvif

Technical Specifications

	SNB-1001N/P
VIDEO	
Imaging Device	1/4" PS CMOS
Total Pixels	680(H) x 512(V)
Effective Pixels	640(H) x 480(V)
Scanning System	Progressive
Min. Illumination	0.7Lux @ (F1.2, 50IRE)
S / N Ratio	50dB
Video Out	SIP connector type, for installation
LENS	
Lens Type	Manual / DC auto iris
Mount Type	C / CS
OPERATIONAL	
Camera Title	Off / On (Displayed up to 15 characters)
Day & Night	Auto (Electrical) / Color / B/W / External
Backlight Compensation	Off / BLC
Contrast Enhancement	SSDR (Samsung Super Dynamic Range) (Off / On)
Digital Noise Reduction	3DNRED (2D+3D noise filter) (Off / On)
Motion Detection	Off / On (4 programmable zones)
Privacy Masking	Off / On (Max 4 points polygonal)
Sync up (Frame Integration)	Off / Auto (2x – 60x)
Gain Control	Off / Low / Medium / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
Electronic Shutter Speed	Auto / A.F.A / Manual (60x – 1/12,000sec)
Flip / Mirror	Off / On
Intelligent Video Analytics	Face detection
Alarm I/O	Input 1ea
NETWORK	
Ethernet	RJ-45 (10/100BASE-T)
Video Compression Format	H.264, MJPEG
Resolution	640 x 480, 320 x 240, 160 x 120
Max. Framerate	Max. 30fps at all resolutions
Video Quality Adjustment	H.264 : Compression level, Target bitrate level control MJPEG : Quality level control
Bitrate Control Method	H.264 : CBR or VBR, MJPEG : VBR
Streaming Capability	Multiple streaming (Up to 10 profiles)
Audio I/O	Mic/Line in , Line out
Audio Compression Format	G.711 a-law
Audio Communication	Bi-directional audio
IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, PPPoE, PPP/TCP, PPP/UDP, RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS
Security	HTTPS(SSL), login authentication, Digest login authentication IP address filtering, User access log, 802.1x Authentication
Streaming Method	Unicast / Multicast
Max. User Access	10 users at unicast mode
Memory Slot	Micro SD/SDHC memory slot
ONVIF Conformance	Yes
Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatian, Hungarian, Greek
Web Viewer	Supported OS : Windows XP / VISTA / 7, MAC OS Supported Browser : Internet Explorer 7.0/8.0, Firefox, Google Chrome, Apple Safari
Control Management Software	NET-i viewer
ENVIRONMENTAL	
Operating Temperature/ Humidity	-10°C ~ +50°C(+14°F ~ +131°F) / 20% ~ 80% RH
ELECTRICAL	
Input Voltage / Current	12V DC / PoE (IEEE802.3af)
Power Consumption	Max. 5.4W (12V DC), Max. 6W (PoE)
MECHANICAL	
Color / Material	Black, Silver / Aluminium, Plastic
Dimensions (WxHxD)	74.3 x 54.5 x 114.4mm (2.92" x 2.15" x 4.50") excluding projections
Weight	160g (0.42 lb)

Dimensions

Unit : mm (inch)

Available Lenses / Accessories (Optional)

SLA-3580DN

SHB-4200H/4200H

Reviews

There are yet no reviews for this product.